

## ECO GYPSUM

### ACRYLIC EMULSION PAINT FOR GYPSUM BOARD EE - 4050

No. TD : E-029/APCT

Revision : 01

Effective Date : 10/08/2021

**ECO GYPSUM Acrylic Emulsion Paint for Gypsum Board EE-4050** is an acrylic emulsion interior paint specially formulated for gypsum board (ceilings and partition).

This product has excellent adhesion to gypsum surfaces & gypsum compound and minimize peeling off the paint from gypsum compound, also minimize ceiling and partition that look uneven from reflected light effect.

**ECO GYPSUM Acrylic Emulsion Paint for Gypsum Board EE-4050** has good adhesion to gypsum board, good hiding power, easy to apply, fast drying and available in interior selection colors.

### PRODUCT DATA

Type	: Acrylic Copolymer Emulsion
Color	: As shown in the color card
Finish	: Matt
Solid by volume	: ± 38.0 %
Specific gravity	: ± 1.55
Theoretical coverage	: 6 - 8 m <sup>2</sup> / kg ( per coat, 30 - 40 Dry Film Thickness ) Depend on film thickness and wastage during application.
Drying time	: Surface dry = 1 hours ( 30° C ) Depend on temperature and humidity
Packaging	: 5 kg, 25 kg
Storage stability	: One year if stored cool and dry and in original not opened container (Do not store below freezing point)

### APPLICATION

Thinning ratio by volume	: 10 % clean water
Application tools	: Brush, Roll, Air spray or Airless spray
Wet film thickness	: 80 – 110 microns ( per coat )
Dry film thickness	: 30 – 40 microns ( per coat )
Recommended dry film	: 60 – 90 microns ( 2 – 3 x 30 microns ), depend on color
Recoating interval	: Minimum : 6 hours ( 30° C ), when the first paint film already dry Maximum : -
Post treatment	: Masking tape is used to protect surface not to be painted, e.g. door and window frames. As the dry film is elastic, cut the line with a knife or a cutter before remove the masking tape.
Cleaning	: Wash all equipment immediately after use with water

### SURFACE PREPARATION

- The gypsum board surface must be dry, clean, sound, and free from all contaminants.
- Remove all loose material or defective paint by thorough brushing and scraping using active fibre brush.
- Treat any areas affected by mould, algae, moss and lichens with **PROPAN Fungicidal Wash**.
- Repair defects with suitable filler. Use ECO EMULSION PLAMUR ECP-4030 for uneven surfaces and crack. Allow to dry.
- It is recommended to apply ECO GYPSUM PRIMER EPG-4049 before applying this coating.

## APPLICATION CONDITION

Temperature	: Minimum 15° C Maximum 50° C
Humidity maximum	: 80 % RH Provide adequate ventilation during application and drying.

## RECOMMENDED COATING SCHEDULE

- Primer coat : ECO Gypsum Primer EPG-4049 without thinning, 1 x 20 microns Dry Film Thickness.
- Finish coat : ECO GYPSUM Acrylic Emulsion Paint for Gypsum Board EE-4050 thinning with 1 part of clean water to 10 parts of paint, 2 – 3 x 30 microns Dry Film Thickness, depend on color.

## SAFETY, SECURITY, HEALTH AND ENVIRONMENT

Do not take internally. This product is non toxic and non flammable. It does not contain any material with heavy metals such as mercury and lead. Avoid contact with the skin and eyes. Higher concentrations produce more severe irritation. Wear suitable protective clothing such as overalls, goggles, dust masks and gloves. Use barrier cream. Wash splashes from skin or eyes immediately. Ensure adequate ventilation and fresh air entry during application and drying. If there are experiences eye watering, headaches, dizziness or difficulty breathing, leave the area to obtain fresh air or wear respiratory protection. If continued difficulty is experienced, get medical attention immediately. Do not breathe vapor or spray mist. Keep away from food, drink and animal feeding stuffs. Dangerous to fish and other aquatic life. Do not contaminate watercourses or ground. This material and its container must be disposed of in a safe way. Avoid all contact with plant life. Close container after each use and keep out of reach of children. Keep in original container, tightly closed, in cool and dry place. Avoid direct sunlight. Keep from freezing. This container is used to storage the paint only. Do not apply to surfaces on which food is prepared. Wash hands and exposed skin before meals and after use. Read all safety, security, health and environment precautions before use.

### First Aid :

- |              |  |
|--------------|--|
| Skin contact | : Wash off thoroughly with plenty of water and soap immediately.<br>Remove contaminated clothing. If irritation occurs, seek medical advice. |
| Eye contact  | : Rinse immediately with plenty of clean water. Seek medical advice.   |
| Inhalation   | : Remove person to fresh air, loosen collar and avoid exertion.<br>Keep patients rested and give artificial respiration.                     |