

# SuperGOLD®

PROPAN Super Gold adalah cat berwarna emas yang mempunyai tampilan kilau seperti emas aslinya. PROPAN Super Gold terbuat dari bahan acrylic emulsion yang dikombinasikan dengan pigmen warna emas pilihan, sehingga warna emasnya berkilau dan tahan lama, tidak mudah pudar, melekat kuat pada substrat, tahan cuaca dan tahan sinar UV matahari.

## Keunggulan

- Warna emas yang berkilau dan tahan lama
- Tahan cuaca
- Warna tidak cepat pudar

PROPAN Super Gold is a gold-colored paint that has appearance like original gold. PROPAN Super Gold is made of acrylic emulsion combined with a special gold pigment that has durable sparkling gold color, not easily to fade, good adhesion to the substrate, weather resistant and UV light resistant.

## Advantages:

- Sparkling gold color and durable
- Excellent weather resistance
- excellent color retention



## Warna emas bernuansa kuning



PROPAN  
Decorcryl DI-400  
Bright Yellow-1203

PROPAN  
Super Gold  
SG-07 WB  
Gold-1230

## Warna emas bernuansa kemerahan



PROPAN  
Decorcryl DI-400  
Geranium-3304

PROPAN  
Super Gold  
SG-07 WB  
Gold-1230

## Tahapan Aplikasi

- 1. Persiapan Permukaan**  
Permukaan substrat harus kering dan bersih serta bebas dari debu, jamur, lumut, minyak, karat atau kotoran lainnya.
- 2. Lapisan Cat Dasar**  
Gunakan cat dasar yang sesuai dengan jenis substrat yang digunakan:
  - Untuk beton atau plesteran semen: PROPAN DECOR Alkali Resisting Primer AS-310 (Solvent Based) atau PROPAN DECOR Alkali Resisting Primer AR-300 (Water Based), 1 kali lapis (1 x 20 mikron), tanpa pengenceran.
  - Untuk besi : Alkyd Primer PROPAN METALKOTE AP-291, 1 kali lapis (1 x 40 mikron).
  - Untuk menutup pori-pori kayu : PROPAN MULTI PURPOSE AQUA PUTTY AWP-919 WB. Setelah kering sempurna, amplas menggunakan kertas amplas no. 180.
- 3. Lapisan Dasar Berwarna**
  - Untuk mendapatkan warna emas bernuansa kekuningan : cat tembok PROPAN DECORCRYL DI-400 Bright Yellow-1203, 2 kali lapis (2 x 30 mikron). Pengenceran dengan air bersih 10 – 20% sesuai kebutuhan aplikasi.
  - Untuk mendapatkan warna emas bernuansa kemerahan : cat tembok PROPAN DECORCRYL DI-400 Geranium-3304, 2 kali lapis (2 x 30 mikron). Pengenceran dengan air bersih 10 – 20% sesuai kebutuhan aplikasi.
- 4. Lapisan Warna Emas**  
PROPAN Super Gold SG-07 WB, 1 kali lapis (1 x 30 mikron). Pengenceran dengan air bersih 10%.
- 5. Lapisan Akhir Clear (jika diperlukan)**  
PROPAN Aqua Stone Care ASC-60 WB, 1 kali lapis (1 x 30 mikron). Pengenceran dengan air bersih 10%.

## Application Procedures

- Surface Preparation**  
Surface must be dry, clean and free from mold, moss, dust, grease, rust and other contaminants.
- Primer Coat**  
Apply primer coat in accordance with the kind of substrate:
  - For concrete or cement plaster : PROPAN DECOR Alkali Resisting Primer AS-310 (Solvent Based) or PROPAN DECOR Alkali Resisting Primer AR-300 (Water Based), 1 coat (1 x 20 microns), without thinning.
  - For metal : Alkyd Primer PROPAN METALKOTE AP-291, 1 coat (1 x 40 microns).
  - For wood : PROPAN MULTI PURPOSE AQUA PUTTY AWP-919 WB. Sanding lightly with sandpaper no. 180.
- Colored Base Coat**
  - For yellowish gold color : PROPAN DECORCRYL DI-400 Bright Yellow-1203, 2 coats (2 x 30 microns), thinning with 10 – 20% clean water according to application needs.
  - For reddish gold color : PROPAN DECORCRYL DI-400 Geranium-3304, 2 coats (2 x 30 microns), thinning with 10 – 20% clean water according to application needs.
- Gold Colored Coat**  
PROPAN Super Gold SG-07 WB, 1 coats (1 x 30 microns), thinning with 10% clean water.
- Clear Coat (optional)**  
PROPAN Aqua Stone Care ASC-60 WB, 1 coats (1 x 30 microns), thinning with 10% clean water.

### Catatan / Notes :

Selang waktu pengecatan minimal 2 jam (tergantung suhu dan kelembaban)  
Recoating interval : minimum 2 hours (depends on temperature and humidity)

