

PROPAN HWO-558

No. TD : H-001
Revision : 00
Effective Date : 29/11/2021

PROPAN HWO-558 is a blend of plant natural oils & waxes offering exceptional durability & resistance for interior wood flooring, doors & kitchen worktops (wood). Produces a quick drying, good water resistance, good hardness and scratch resistance. This product is easy to apply, resulting smooth natural satin finish and simple repair if there is spot/local damage.

PRODUCT SPECIFICATION

Type : Blend of natural oils & natural waxes
Soid Content : 50± 2 %
Flash Point : 35°C
Packing : 1 lt. in steel can

APPLICATION

Application condition : 25 - 35°C, 60 - 80%RH
Application method : wipping
Substrate : Teak or other solid wood
Application viscosity (30°C) : 15 – 25 sec Din 4 by wipe (ready for use)
Pot life of mixture : N/A
Coating Amount (wet) : 20 - 30 g/m² of mixture per coat
Theoretical coverage : 30 m²/lt. at ca 30 g/m²

FILM PROPERTIES

Drying time (at 30°C, RH = ± 80%)
▪ Dust Free : 20 - 30 minutes
▪ Tack Free : 3 - 4 hours
Recoating time : wet on dry = after 4 - 5 hours

OTHERS

Shelf life : Three years if stored in cool and dry condition in original sealed can.
Storage and handling : Store in good ventilation room temperature.

SURFACE PREPARATION

1. The surface must be clean, dry, and free from oil.
2. Remove oil, grease, or dirt with solvent or appropriate method (wire brush, steel wool, or sand paper no. 120 - 150 for Oak wood, no. 150 - 180 for Rubber and Ramin wood, and no. 180 followed by 240 for Cherry wood).

APPLICATION INFORMATION

1. Mix well the **PROPAN HWO-558** should be stirred throughhly before and during use. Containerrs whith difeferent bacht numbers should be mixed to avoid colour mismatch
2. Apply a thin layer of oil using a short-brisled pain roller(3-4 mm) or similar, along the grain of the wood. Distribute the oil thoroughly
3. leave it to dry for 4 – 5 hours. Drying time will vary by temperature, humidity and application quantity. Lower temperatures and/or higher humidity can extend dring time.

4. Repeat the treatment within 24 hours if another coat of oil is required. A single coat of oil is normally enough for previously-oiled surface

SAFETY PRECAUTION

This product does not contain formaldehyde. Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust masks, and solvent resistance gloves. Use barrier cream.

This product is flammable. Do not smoke. Use only explosion proof equipment. Do not breathe the vapor of spray. Avoid contact with strong oxidizing agents and water.

FIRST AID:

- Eye contact : Rinse immediately with plenty of water for at least 15 minutes; seek medical advice
- Skin contact : Wash with soap and water. If irritation occurs, seek medical advice
- Ingestion : Provide symptomatic treatment and seek medical advice
- Inhalation : Remove person to fresh air. Keep patient rested and give artificial respiration

DISCLAIMER

This document contains information issued based on the best and latest of Propan's knowledge in accordance to laboratory testing and practical application experience. The end user must test the product's suitability for their specific application and purpose. Propan shall not be liable for defects where the application of the Product has not been made fully in accordance with the recommendations and requirements. This document is subjected to change without further notice. Please consult Propan for any specific guidance on the suitability of this product for their needs or for any specific application practices.