

PROPAN AQUA STONE CARE

Pelapis Batu Alam

No. TD : P-137
Revision : 00
Effective Date : 25/10/2022

PROPAN AQUA STONE CARE ASC-60 WB is a natural stone coating which is made of acrylic emulsion, with glossy appearance. It provides maximum protection to the surface of natural stone and accentuate the beauty of natural stone without changing the natural color of natural stone. This quality provides good adhesion to the substrate, good weather resistance, fungus resistance and suitable for indoor or outdoor uses.

PRODUCT DATA

Type	: Acrylic emulsion
Appearance	: Milky liquid
Color	: Clear transparant
Finish	: Glossy
Solid by volume	: 30 - 35 %
Specific gravity	: 1 – 1.05
Theoretical coverage	: 6 – 10 m ² /litre (1 coat, depend on the substrate absorption)
Drying time	: 2 hours (30°C)
Packaging	: 1 litre, 2.5 litres
Storage and handling	: Store in cool and dry condition in original unopened packaging. Protect from dampness and direct sunlight. Mix before use

APPLICATION

Thinning ratio by volume	: Ready to use
Application tools	: Brush
Substrate	: Natural stone
Recommended dry film thickness	: 60 microns (2 – 3 coats)
Recoating interval	: Minimum 2 hours (30°C), when the first film already dry Maximum –
Thinner/clean up	: Clean water
Cleaning	: Wash all equipment immediately after use with clean water

SURFACE PREPARATION

- The surface must be clean, dry, sound and free from all contaminants.
- Remove all loose material by thorough brushing and scraping using active fibre brush.
- Treat any areas affected by mold, algae, moss and lichens with **PROPAN FUNGICIDAL WASH**.

APPLICATION CONDITION

Temperature	: 25 - 35°C
Humidity maximum	: 80 % RH

Provide adequate ventilation during application and drying.

RECOMMENDED COATING SCHEDULE

- Preceding coat : PROPAN AQUA STONE CARE ASC-60 WB, 1 coat
- Subsequent coat : PROPAN AQUA STONE CARE ASC-60 WB, 1 – 2 coats

SAFETY PRECAUTIONS

PROPAN AQUA STONE CARE ASC-60 WB is non toxic and non flammable and does not contain heavy metals in its materials such as lead. Avoid contact with skin and eyes. Do not inhaled. Wear suitable protective equipment such as googles, dust mask and gloves. For more information refer to material safety data sheet.

First Aid

- Skin contact : Wash with soap and water. If irritation occurs, seek medical advice
- Eye contact : Rinse immediately with plenty of water. Seek medical advice if irritation persists.
- Inhalation : Take the person out to get more fresh air, loosen collar and avoid exertion. Keep patient rested and help using breathing apparatus.

Disclaimer

This document contains information issued based on the best and latest of Propan's knowledge in accordance to laboratory testing and practical application experience. The end user must test the product's suitability for their specific application and purpose. Propan shall not be liable for defects where the application of the Product has not been made fully in accordance with the recommendations and requirements. This document is subjected to change without further notice. Please consult Propan for any specific guidance on the suitability of this product for their needs or for any specific application practices.